

Pyure Mini®

Air & Surface Protection

Product Specifications



PORTABLE

Pyure Mini Purifier

The Pyure Mini air purifier is designed for small spaces where a quiet and modern portable unit is sought. It is ideal for offices and classrooms, conference and waiting rooms, and other commercial applications that are seeking to purify and deodorize small indoor spaces.

Operating Guideline

	Pyure Mini 25	Pyure Mini 50
Treatment Range	80 – 250 ft ² (8 - 23 m ²)	250 – 500 ft ² (23 - 46 m ²)

The table above summarizes the treatment area under typical operating conditions:
3 air changes per hour, 90% recirculated air, and 9 foot (2.7 m) ceiling.

Specifications

Dimensions (LxWxD)	12" x 14.4" x 4" (304.8mm x 365.76mm x 101.6mm)
Weight	9lbs (4.08kg)
Voltage	120V @ 60Hz / 230V @ 50Hz
Power	100 Watts (Max)
Number of Optics	1
Noise Level	39 to 48dB
Airflow*	16 CFM *Airflows were measured with new/clean units
Filter	Washable 10.5" x 2.75" x 0.25" (266.7mm x 69.85mm x 6.36mm)
Shipping Dimensions	16" x 18.4" x 7.75" (406.4mm x 467.36mm x 196.85mm)
Shipping Weight	12lbs (5.44kg)
Certification	EN/UL/CSA 60335, CE, RoHS, REACH
Warranty	2 years covering defects in workmanship or materials, but excluding spare parts and consumables

Distributør:



post@friskerom.no

+47 92 81 00 83



Copyright 2025, The Pyure Company.
Pyure Mini® is a trademark of The Pyure Company,
Boynton Beach, FL 33426 USA
Document# PMNXXLS000